

| Cable Winch SAFE WORK METHOD STATEMENT (SWMS) | | | | | | | | |
|--|---|---|-------------------------------------|--|--|--|--|--|
| | TASK OR ACTIVITY: Cable Winc | h | | | | | | |
| Business Name: [Company Name] | | ABN: [ABN] | SWMS# | | | | | |
| Business Address: [Company Address] | | | | | | | | |
| Contact Person: | Phone: [Phone] | E fil: | | | | | | |
| THIS SAFE WORK METHOD | STATEMENT IS APPROVED BY | THE PLOOF THE PROJECT | | | | | | |
| Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts. | cting a business or undertaking (r 3U) is | required to ture at a safe work method s | statement (SWMS) is prepared before | | | | | |
| Full Name: | | | | | | | | |
| Signature: | | Title: | Date: | | | | | |
| Details of the person(s) responsible for ensuring implementation, monitoring | compliance of the SWMS well as review | s and modifications of the SWMS. | | | | | | |
| Full Name: | | Title: | Phone: | | | | | |
| ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS WMS. ST HAVE THE FOLLOWING COMMUNICATED | | LL RELEVANT PERSONNEL WHO HAVE B PMENT AND APPROVAL OF THIS SWMS | EEN CONSULTED AND | | | | | |
| Safety meetings or toolbox talks will be sched ed in accordance with agislative requirements to first identify any site hazards, conditions unical those hazards and then to further take steps to either the conditions of the cond | NAME | SIGNATURE | DATE | | | | | |
| If an incident or a near miss occurs, all work must standardly. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity. | | | | | | | | |
| Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel. | | | | | | | | |
| The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident. | | | | | | | | |



| | | CL | IENT OR PRINCIPAL | CONTRACTOR D | DETAILS | | | | |
|----------------------------|-------------------------------|--------------------------------|-----------------------|---|---|------------------------|--------------|--|--|
| Client: | | | | | | SCOPE OF WORKS | | | |
| Project Name: | | | | Provide a detailed description | n of the specific work being | carried out (otherwise | | | |
| Project Address: | | | | | known as cope of works). | | | | |
| Project Manager: | | | | | | | | | |
| Contact Phone: | | | | | | | | | |
| Project Manager Sig | gnature: | | | | | | | | |
| Date SWMS supplie | ed to Project Manager: | | | | | | | | |
| | | ANY HIGH | RISK CON PUCT | N' JRK BEING | CARRIED OUT | | | | |
| ☐ involves a risk of a p | erson falling more than 2 n | neters. | | is carried out on or near pressurised gas mains or piping. | | | | | |
| ☐ is carried out on a te | lecommunication tower. | | M + M | is carried out on | is carried out on or near chemical, fuel or refrigerant lines. | | | | |
| ☐ involves demolition of | of an element of a structure | that is load-be | | is carried out on | is carried out on or near energised electrical installations or services. | | | | |
| ☐ involves demolition of | of an element related to the | e physical integrit of a str | 3 | is carried out in an area that may have a contaminated or flammable atmosphere. | | | | | |
| ☐ involves, or is likely t | o involve, disturbing a es | stos. | | involves tilt-up or precast concrete. | | | | | |
| ☐ involves structural al | teration or repair that re | upp to p | prevent collapse. | is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor. | | | | | |
| is carried out in or ne | ear a confined space. | | | ☐ is carried out in an area of a workplace where there is any movement of powered mobile plant. | | | | | |
| ☐ is carried out in/near | a shaft or trench deeper th | nan 1.5m or tunnel involvir | ng use of explosives. | is carried out in areas with artificial extremes of temperature. | | | | | |
| is carried out in or ne | ear water or other liquid tha | at involves a risk of drowning | ng. | involves diving v | vork. | | | | |
| | | ANY H | IGH-RISK MACHINER | RY OR EQUIPMEN | NT NEARBY | | | | |
| ☐ Forklift | ☐ Crane/s | ☐ Hoist/s | ☐ Excavator | ☐ Backhoe/Loader | Boom Lift | □ EWP | ☐ Genie Lift | | |
| ☐ Trencher | ☐ Drilling Rig | Trucks | Formwork | ☐ Bobcat | ☐ Flammable Gas | ☐ Fuel | ☐ Dozer | | |
| ☐ High Voltage | ☐ Mulcher | ☐ Tilt-up Panels | Roller | ☐ Scissor Lift | ☐ Tractor | ☐ Other - | | | |





FOOT HAND **HEAD HEARING** SPIRATORY FACE HIGH-VIS **PROTECTIVE** FALL SUN HAIR/JEWELLERY CLOTHING **PROTECTION PROTECTION** PROTECTION **PROTECTION** PROTE DTECTION **PROTECTION** CLOTHING **PROTECTION PROTECTION SECURED**

Select me appropriate PPE above suitable for the equipment used or the job task being performed (if applicable).

Note: A SWMS must be reviewed regularly to make sure it remains effective. A SWMS must be reviewed (and revised if necessary) if relevant control measures are revised. The review process should be carried out in consultation with workers (including contractors and subcontractors) who may be affected by the operation of the SWMS and their health and safety representatives who represented that work group at the workplace.

When a SWMS has been revised, the person conducting a business or undertaking must ensure all:

- 1. persons involved in the work are advised that a revision has been made and how they can access the revised SWMS;
- 2. persons who will need to change a work procedure or system as a result of the review are advised of the changes in a way that will enable them to implement their duties consistently with the revised SWMS: and.
- 3. workers that will be involved in the work are provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|-----------------------|---------------------------------------|-----------------|---|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| 1. Preparation | Trip hazards, Falling objects | 2M | - Conduct a pre-start inspection of the work area to identify and remove any potential trip hazards, such as loose cables, debris, or tools. - Clearly mark walkways and paths with high-vir sully tape or paint to minimise the risk of trips and falls in the work area. - Implement effective housekeeping practices the classing up spills, putting away tools after use, and maintaining a well-organist took area. - Provide appropriate person corotective equipms (PPE) for workers, including non-slip footwear, hard hats, a whigh-visibility vest. - Ensure all employs and the last of the movement and wrage of interials is well as other use of cable winches and associated endoment. - More weath a conditions closely ansupostpone work if conditions are unfavorable (e.g., is a virain, but givinds, or poor visibility). - Erection andes on aution tape around the work area to prevent unauthorised access and he gate the list of falling objects. - Develo a liftingulan that considers the weight, size, and shape of the load, as well as or rectired height and distance of the lift. - Inspect or rigging equipment prior to use, ensuring that it is in good condition and as from defects. - Use proper lifting techniques and taglines when moving materials, in order to maintain control of the load and prevent it from swinging or falling. - Designate a spotter to keep an eye out for potential hazards and guide the winch operator during lifting operations. - Establish clear communication protocols between the winch operator, spotter, and other workers in the area, utilising hand signals, radios, or other agreed-upon communication methods. - Schedule regular breaks for workers to reduce fatigue and maintain focus on safety procedures. - Conduct periodic safety briefings and toolbox talks to reinforce the importance of following safe work practices and encourage open communication about potential hazards or concerns. | 1L | |
| 2. Pre-Use Inspection | Electrical hazards, Damaged equipment | 3Н | - Regular inspection of electrical cables and equipment: Ensure that all electrical cables, outlets, switches, and equipment are in good working condition and free from visible damages or frayed wires. - Perform a comprehensive pre-use inspection: Before using the cable winch, always conduct a thorough inspection to identify any potential hazards or defects that may have developed during storage, transit, or prior use. | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|---------------------|------------------------------------|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | Proper training for workers: Ensure that workers operating the cable winch have received adequate training in its use, as well as the recognition and avoidance of potential hazards associated with its operation. Ensuring appropriate Personal Protective Egyptient (PPE): Workers should wear appropriate PPE, including gloves, safety of uses, and boots when operating the cable winch. Using insulated handling tools: When encount the electrical hazards during presuse inspection, use insulated handling tools to present direct or back with live components. Lockout/Tagout presences: Incoment proper lock usagout procedures to ensure the cable winch the e-energied of one group inspection and maintenance activities. Checking to be winch lost aspacity uspendie load capacity of the cable winch before the analysis of the cables, broken pulleys, or bent hooks, according to established company procedures. Disposition of dame and equipment: Remove and properly dispose of any damaged equipment, which as a need cables, broken pulleys, or bent hooks, according to established company procedures. Integer at less to all equipment: Ensure easy access to the cable winch and other related to prend during the pre-use inspection, and keep the surrounding area lear or pructions. Inporting hazards and incidents: Encourage workers to report any observed has afted or incidents related to the cable winch immediately to supervisors for prompt action. Maintenance records: Maintain detailed records of regular inspections, routine maintenance, and repairs, and provide these records as needed for internal or external audits. Implementing an incident response plan: Have a well-defined incident response plan in place to appropriately address any accidents, injuries or hazardous situations that may occur during | | |
| 3. Area Setup | Falls from height, Poor visibility | 2M | - A thorough site inspection and hazard identification must be conducted prior to beginning work to address potential risks, such as falls from height and poor visibility. - Employ appropriate fall protection equipment and systems, including but not limited to harnesses, lanyards, anchorage points, guardrails, and handrails. - Ensure adequate lighting is in place to address visibility concerns; this may include the use of portable lighting or temporary floodlights on the worksite. | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|-------------------------------|---|-----------------------|---|------------------------|--------------------|
| JOB STEP SPECIFIC WORK STEPS | POTENTIAL HAZARDS HAZARDS THAT MAY ARISE | IR INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS - Mark off a designated 'work zone' with clearly visible signage and barricades, separating the area from other areas of the worksite and preventing unauthorised access. - Regularly inspect and maintain all cable winely addipment, including wire ropes, pulleys, shackles, and slings, to ensure the one in good working order and free from defects. - Train all workers involved in the setup of the converted system on how to safely operate the equipment and perform tasks associated with the work step. - Establish clear communication protocols between the order to be step. - Establish clear communication protocols between the order to coordinate tasks effectively and the critical afety information, calcularly when visibility is limited. - Plan ahead and prepare for adversary earth conditions that may affect visibility, such an fog, do not rain to implement the extra precautions or delaying work if neces. | RR RESIDUAL RISK | |
| | | | Utilis placer personal protective equipment (PPE) at all times, such as high-visibility closers, har coats, safety glasses, and gloves. Develor an emergency response plan detailing steps to be taken in case of a fidents or includes its involving falls or visibility concerns, and ensure all workers are familiary with the plan. Conduct egular toolbox talks and safety briefings to remind workers of their repossibilities regarding area setup, hazard identification, risk management, and sale work practices. Implement a systematic approach to housekeeping, ensuring the work area is kept clean and free of debris or tripping hazards that could compromise safety. Foster a safety culture that encourages workers to be proactive in identifying and reporting hazards or concerns, providing constructive feedback for continuous improvement. | | |
| 4. Winch Positioning | Crushing hazards, Pinch points | 3Н | | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|---------------------|--|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |
| 5. Attaching Load | Manual handling injuries, Entanglement | 2M | | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|---------------------|--|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |
| 6. Operation | Entanglement, Inadequate communication | 3Н | | 2M | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|---------------------|------------------------|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|---------------------|------------------------|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |
| 7. Cable Tensioning | Ejected parts, Overlog | | | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|------------------------|-------------------------------|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |
| | | | | | |
| 8. Monitoring Progress | Poor visibility, Nois mazards | 1L | | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|---------------------|--|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |
| 9. Releasing Load | Loss of control, Manual handling tries | 2M | | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|-----------------------|---------------------------------------|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| 10. Winch Maintenance | Chemical exposure, Electrical hazards | | | 2M | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|----------------------------------|---------------------------------|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| 11. Post-Operation Inspection | Damaged equipment, Trip hazards | 1L | | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|----------------------------|---|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |
| 12. Cleanup and Storage | Slips, trips and falls, Chemical exposure | 2M | | 1L | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR | RESPONSIBLE PERSON |
|---------------------|------------------------|-----------------|--|------------------|--------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK | NAME OF PERSON |
| | | | | | |
| | | | | | |
| | | | | | |



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

 $\textbf{Legislation QLD:} \ \underline{\textbf{https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws}$

Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislat

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis > odes-or racti

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 2011

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/wo_place-

Codes of Practice NT: https://worksafe.nt.gov.au/s

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/legislation

Codes of Practice for SA: https://www.safework.sa.gov.au/work_aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Occupational Health al. Safety Act

Occupational Health and afety gulations 2017

Legis on VIC: https://www.csafe.vic.gov.au/occupational-health-and-safety-act-and-

<u>qulat.</u>

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work



SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

| Tollow any sale work instructions which are provided, and agrees to use an reisonal riotective Equipment where appropriate. | | | | | | | | |
|--|-----|------------|----------------|---|----------------------------|------------|----------|--|
| Worker Name | Pos | sition | Signature | Date | Time | Sup | pervisor | |
| | | | | Date: | | | | |
| | | | | _ | | | | |
| | | | | Date | | | | |
| | | | | l te: | | | | |
| | | | AV | Date: | | | | |
| | | | | Date: | | | | |
| | | | | Date: | | | | |
| Date: | | | | | | | | |
| | | SAF WO A S | THUD STATEMENT | MONITORING AND | REVIEW | | | |
| The SWMS must be reviewed regularly to the ke sure it remains effective and must be reviewed (and revised if necessary) if relevant control measurements are subcontracted by the operation of the SWMS and their health and safety representatives who research that work group at the workplace. When the SWMS has been revised the PCBU must ensure that all persons involved with the work are advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a result of the review are advised of the changes in a way that will enable them to implement their duties consistently with the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist | | | | The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to: 1. Spot Checks. 2. Consultation with workers, contractors and sub-contractors. 3. Internal audits on a continual basis. An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures | | | | |
| them to understand and imp | | | | | tently developing ever-imp | 3 , | · ' | |
| REVIEW NUMBER | 1 | □ 2 | □ 3 | □ 4 | □ 5 | □ 6 | □ 7 | |
| NAME | | | | | | | | |
| INITIALS | | | | | | | | |
| DATE | | | | | | | | |



SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

| ITEMS WHICH MUST BE INCLUDED IN THE SWMS | COMPLETED | TO BE DONE | COMMENTS |
|---|-----------|------------|----------|
| | | | |
| The company details have been entered, including the project name and address. | | | |
| Names and signatures of all relevant personnel consulted during the development of the SWMS. | | P P | |
| Name, signature, position and date signed of the person approving the SWMS. | | | |
| Specific personnel and qualifications, experience is noted in the SWMS. | P | | |
| Provides a step-by-step process of tasks required to carry out the activity or task. | | | |
| Adequate risk assessment of any identified hazards has been completed. | | | |
| Foreseeable hazards are identified and documented for each step. | | | |
| Any hazards listed in any site risk assessments have been added to the SWh | | | |
| SWMS initial risk (IR) column as well as residual risk (RR) columns completed. | | | |
| Check control measures added to the SWMS are the most effecting so tions. | | | |
| Responsible person is assigned and listed on the SWMS for the imperent of continue assures. | | | |
| Permit requirements specified, such as Hot Work, Veralt Heights etc. | | | |
| SWMS identifies plant and equipment to be u d. | | | |
| Details of inspection checks required for any equipment listed are noted on the SWMS. | | | |
| Describes any mandatory qualifications, experience raining skills required to perform the work. | | | |
| Applicable personal protective equipment is selected on the SWMS. | | | |
| Lists any required permits or licenses. | | | |
| Reflects and documents any legislative references and/or Australian Standards. | | | |
| dentifies any hazardous substances used with specific control measures in line with any SDS. | | | |
| | | | |
| REVIEWED BY | DATE R | EVIEWED | |
| SIGNATURE | DATE CO | MPLETED | |